

PowerShot SX740 HS

LITE EDITION

TELL YOUR STORY IN 4K WITH CANON'S POWERFUL 40X TRAVEL SUPERZOOM



With 40x optical zoom, superfast DIGIC 8 processing and spectacular 4K movie resolution in a pocket-sized body, the powerful PowerShot SX740 HS LITE EDITION redefines travelling light.

24mm
WIDE **40x**
40x



20.3 MEGA PIXELS
HIGH-SENSITIVITY CMOS **20.3 Megapixel**

10
Frames Per Sec **10 fps**

4K
UHD **4K**

5-axis
5-Axis Digital IS



Canon



Travel with 40x optical zoom in your pocket

Measuring just 39.9 mm deep, the PowerShot SX740 HS LITE EDITION boasts huge 40x optical zoom, doubling to 80x with ZoomPlus.



Capture memories in 4K Ultra High Definition

Spectacular 4K movie resolution and 5-axis stabilisation captures incredible detail, even at a distance.



Confidently shoot 20.3 Megapixel photos

Canon's DIGIC 8 processor intelligently detects the scene and subject, managing camera settings with Zoom Framing Assist and Hybrid Auto.



Share and store photos with Wi-Fi and Auto Transfer

Stay connected with Wi-Fi and Bluetooth® connectivity and keep your precious memories safe with Auto Transfer.



Never miss a moment thanks to fast shooting speeds

Snap superfast shots at exactly the right moment, with incredibly responsive shutter release and 10 fps continuous shooting.

PRODUCT RANGE



PowerShot SX740 HS LITE EDITION

TECHNICAL SPECIFICATIONS

PowerShot SX740 HS

LITE EDITION

RANGEFINDER		LCD MONITOR	
Range	-	Type	Tilt up Approx. 180 degrees 7.5 cm (3.0") LCD (TFT), approx. 922,000 dots
Ranging Accuracy	-	Coverage	Approx. 100%
Increment Reading	-	Brightness Adjustment	Adjustable to one of five levels
Magnification	-	Touch-Screen Operations	-
Rangefinder Specific Functions	-	Display Options	-
Laser Classification	-		
		FLASH	
IMAGE SENSOR		Modes	Auto, Manual Flash On / Off, Slow Synchro
Type	1/2.3 type back-illuminated CMOS	X-Sync	Yes. Fastest speed 1/2000 s
Effective Pixels	Approx. 20.3M ¹	Flash Exposure Compensation	+/- 2 EV in 1/3 stop increments.
Total pixels	Approx. 21.1M	Built-in Flash Range	50 cm – 5.0 m (W) / 2m - 2.5 m (T)
Colour Filter Type	Primary Colour	Flash Exposure Lock	Yes
		Second Curtain Synchronisation	-
IMAGE PROCESSOR		Hot Shoe/PC Terminal	-
Type	DIGIC 8		
		SHOOTING	
LENS		Modes	Smart Auto (29 scenes detected), Hybrid Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Sports, SCN
Focal Length	4.3 – 172.0 mm (35 mm equivalent: 24 – 960 mm)	Picture Styles	-
Zoom	Optical 40x Zoom Plus 80x Digital approx. 4.0x (with Digital Tele-Converter Approx. 1.6x or 2.0x ²) Combined approx. 160x	Drive Modes	Single, High-speed continuous, low-speed continuous
		Continuous Shooting	Max: One Shot AF approx 10fps for approx. 59 shots, Servo AF approx 7.4fps for approx. 127 shots ³
Maximum f/number	f/3.3 – f/6.9		
Construction	13 elements in 11 groups (1 Hi-UD lens, 3 UD lenses, 2 double-sided aspherical lenses, 1 single-sided aspherical lens)	FILE TYPES	
Image Stabilisation	Yes (lens shift-type), Approx. 3.5-stops ³ . Intelligent IS with Dual Sensing IS plus 5-axis Advanced Dynamic IS	Still Image Type	JPEG compression, (Exif 2.3 [Exif Print] compliant) / Design rule for Camera File system 2.0, Digital Print Order Format [DPOF] Version 1.1 compliant
Real Field of View (Stills)	-	RAW+JPEG/HEIF Simultaneous Recording	-
Real Field of View (Movie)	-	Image Size	4:3 - (L) 5184 x 3888, (M) 3648 x 2736, (S) 2432 x 1824 16:9 - (L) 5184 x 2912, (M) 3648 x 2048, (S) 2432 x 1368 3:2 - (L) 5184 x 3456, (M) 3648 x 2432, (S) 2432 x 1616 1:1 - (L) 3888 x 3888, (M) 2736 x 2736, (S) 1824 x 1824 Resize option available in playback
Apparent Field of View (Still)	-		
Apparent Field of View (Movie)	-	RECORDING PIXELS / COMPRESSION	
1000m Field of View (Still)	-	Movie Type	MP4 [Video: MPEG-4 AVC / H.264, Audio: MPEG-4 AAC-LC (stereo)]
1000m Field of View (Movie)	-	Movie Size	(4K) 3840 x 2160, 29.97/25 fps (Full HD) 1920 x 1080, 59.94/50/29.97/25 fps, (HD) 1280 x 720, 59.94/50 fps Up to 29 min 59s ⁵
		Movie Length	Maximum Recording Bitrate at 4K Approx. 120 Mbps
FOCUSING		Bitrate/Mbps	Built-in stereo microphone
Type	TTL (Contrast AF)	Microphone	Built-in speaker
AF System/Points	Face & Tracking (9 points), Tracking, Zone, 1-point, Center	Speaker	With info display, no sound
AF Modes	One Shot, Servo, Continuous	HDMI Display	Type D (With HDMI output to HDR compatible TVs)
AF Point Selection	-	HDMI Output	AF / MF
AF Lock	-	Focusing	4K: 100-1600FullHD (50p/60p): 100-2000FullHD (25p/30p): 100-3200 HD: 100-2000
AF Assist Beam	Yes	ISO	
Manual Focus	Yes, plus MF Peaking		
Focus Bracketing	-	OTHER FEATURES	
Closest Focusing Distance	1 cm (W) from front of lens in Macro	GPS	GPS via Mobile (via Canon Camera Connect app with compatible smart devices) ⁶
		Red-Eye Correction	Yes, during shooting and playback
EXPOSURE CONTROL		My Camera / My Menu	-
Metering modes	Evaluative, Centre-weighted average, Spot (Centre)	My Category	-
AE Lock	Yes	Intelligent Orientation Sensor	
Exposure Compensation AEB	+/- 3 EV in 1/3 stop increments	Histogram	Yes, during playback
ISO Sensitivity	100-3200 in 1 stop increments	Self Timer	Approx. 2, 10 s or Custom
		Menu Languages	English, German, French, Dutch, Danish, Finnish, Italian, Greek, Norwegian, Portuguese, Russian, Swedish, Spanish, Ukrainian, Polish, Czech, Hungarian, Turkish, Simplified Chinese, Chinese (traditional), Japanese, Korean, Thai, Arabic, Romanian, Farsi, Hindi, Malay, Indonesian, Vietnamese, Hebrew
SHUTTER			
Speed	15 - 1/3200 s		
WHITE BALANCE			
Type	-		
Settings	Auto, Daylight, Shade, Cloudy, Tungsten, Fluorescent, Custom.		
VIEWFINDER			
Type	-		
Dot count	-		
Coverage (Vertical/Horizontal)	-		
Magnification	-		
Dioptr Correction	-		
Refresh Rate	-		

TECHNICAL SPECIFICATIONS

PowerShot SX740 HS
LITE EDITION

CONNECTIVITY

Wired Connectivity

Hi-Speed USB dedicated connector (Micro-B compatible) for data transfer. USB charging: Not supported

Wireless Connectivity

Wi-Fi (IEEE802.11b/g/n), (2.4 GHz only)⁷, Bluetooth low energy technology

Other

HDMI Micro (Type-D) Connector

DIRECT PRINT

PictBridge

Yes (via USB or Wireless LAN)

Canon Printers

Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting Pict Bridge

STORAGE

Type

SD, SDHC, SDXC (UHS-1 Speed Class 3 compatible)

SUPPORTED OPERATING SYSTEM

PC

Windows 11 / 10 / 8.1 / 8 / 7 SP1
For Wi-Fi connection to a PC: Windows 10 / 8.1 / 8 / 7 SP1
For Image Transfer Utility: Windows 11 / 10 / 8.1 / 8 / 7 SP1

Macintosh

Mac OS X 10.9 / 10.10 / 10.11
For Wi-Fi connection to a PC: Mac OS X 10.9 / 10.10
For Image Transfer Utility: Mac OS X 10.9 / 10.10 / 10.11 / 10.12 / 10.13 / 10.14 / 10.15

SOFTWARE

Image Processing

-

Other

Image Transfer Utility Camera Connect app available on iOS and Android devices

Browsing & Printing

POWER SOURCE

Batteries

Rechargeable Li-ion Battery NB-13L (battery and charger supplied)

Battery Life

Approx. 265 shots⁹Eco Mode: Approx. 370 shots
Playback Mode: Approx. 240 min

Battery Indicator

4 state on LCD

Power Saving

Eco mode (On / Off)
Power saving options:
- Display Off time
- Auto power Off time

Power Supply & Battery Chargers

Battery Charger CB-2LHE (USB charging: Not supported)

ACCESSORIES

Soft Case / Waterproof Case

PU Leather soft case DCC-2400 Black

Lenses

-

Power Supply & Battery Chargers (Optional)

Battery Charger CB-2LHE (USB charging: Not supported)

Flash

-

Remote Controller/Switch

Remote shooting and playback via Canon Camera Connect app.

Other

Interface cable IFC-600PCU

PHYSICAL SPECIFICATIONS

Operating Environment

0 – 40 °C, 10 – 90% humidity

Water/Dust-Resistance

-

Dimensions (WxHxD)

110.1 x 63.8 x 39.9 mm⁹

Weight

Approx. 299 g (including battery and memory card)⁹

Footnotes:

[1] Image processing may cause a decrease in the number of pixels.

[2] Depending on the image size selected.

[3] Based on the CIPA guidelines. Values at maximum optical focal length. Cameras whose focal length exceeds 350 mm (35 mm equivalent) are measured at 350 mm.

[4] Sustained continuous shooting speed is tested based on Canon's testing standard.

Function requires compatible SDHC/SDXC UHS-I Speed Class 3 memory card, total number of frames captured varies depending on shooting subject, settings and brand of memory card

[5] The following Speed Class memory cards are required for maximum record time: (HD) 1280 x 720 SD Speed Class 4 or above. (Full HD) 1920 x 1080 SD Speed Class 10 or above. (4K) 3840 x 2160 UHS Speed Class 3 or above.

[6] GPS use may be restricted in certain countries or regions. Use of GPS should comply with the laws and regulations of the country and area in which it is being operated including any restriction on the use of electronics.

[7] Wi-Fi use may be restricted in certain countries or regions. Wi-Fi support varies by device and region.

[8] Software applications compatible with Windows 10 in Windows 10 Desktop Mode only

[9] Based on the CIPA guidelines

Disclaimers

Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.

App Store and macOS are trademarks of Apple Inc., registered in the U.S. and other countries.

Google Play and Android are trademarks of Google LLC.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

HDMI, HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

The Wi-Fi CERTIFIED logo and the Wi-Fi Protected Setup mark are trademarks of the Wi-Fi Alliance.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Canon Inc. is under license. Other trademarks and trade names are those of their respective owners.

All other trademarks are the property of their respective owners.

All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated.
Subject to change without notice.

TELL YOUR STORY IN 4K WITH CANON'S POWERFUL 40X TRAVEL SUPERZOOM

PowerShot SX740 HS
LITE EDITION

With 40x optical zoom, superfast DIGIC 8 processing and spectacular 4K movie resolution in a pocket-sized body, the powerful PowerShot SX740 HS LITE EDITION redefines travelling light.



What's in the box

PowerShot SX740 HS LITE EDITION

- PowerShot SX740 HS LITE EDITION
- Wrist Strap WS-800
- Battery Pack NB-13L
- Battery Charger CB-2LHE
- AC Cable (E)
- User Manual Kit

PowerShot SX740 HS LITE EDITION TRAVEL KIT

- PowerShot SX740 HS LITE EDITION
- Wrist Strap WS-800
- Battery Pack NB-13L
- Battery Charger CB-2LHE
- AC Cable (E)
- User Manual Kit
- Joby GorillaPod
- Travel Case DCC-2400



Canon